


## Cepex-veggkontakt, grå

Bestillingsnr. 4105



- Skrukontakt
- Ballsikker iht. DIN 18032

## Tekniske spesifikasjoner

Ampere	16 A
Poler	5 p
Volt	400 V
Klokkeposisjon	6 h
Hertz	50-60 Hz
Kapslingsgrad	IP44
Berøringsbeskyttelse	false
Vekt	307 g
Kontrollmerke	VDE, EAC, CQC

## Dimensjoner

Drawing 1 MB 312	Amp. Poles	16			32		
		3	4	5	3	4	5
Dim. in mm	a	93	93	93	93	93	93
	b	90	90	90	90	90	90
	c	87	87	87	99	99	99
	d	75	75	75	75	75	75
	e	73	73	73	73	73	73
	f	5.5	5.5	5.5	5.5	5.5	5.5
	g	4.2	4.2	4.2	4.2	4.2	4.2
	k	33	33	33	33	33	33
	y	25.5	25.5	25.5	25.5	25.5	25.5
	M	25x1.5	25x1.5	25x1.5	25x1.5	25x1.5	25x1.5
Terminal for cond. cross section (mm <sup>2</sup> ) min.-max.		1.5 1.5 1.5	2.5 2.5 2.5	2.5 2.5 2.5	1.5 1.5 1.5	2.5 2.5 2.5	2.5 2.5 2.5
		-4 -4 -4	-6 -6 -6	-6 -6 -6	-4 -4 -4	-6 -6 -6	-6 -6 -6