

AMAXX®-kontaktkombinasjon

Bestillingsnr. 920009




- Kablet og klart til bruk
- Sidehengslet hus
- Hus og boksinnsetts av [AMAPLAST](#)
- Sikring under transparent betjeningsklaff

Tekniske spesifikasjoner

CEE 16 A, 5 p, 400 V	1
SCHUKO®	2
Fusing	<ul style="list-style-type: none"> • 1 jordfeilbryter 40 A, 4 p, 0,03 A • 1 automatsikringer 16 A, 3 p, C • 2 automatsikringer 16 A, 1 p, C
Forankoblet sikring maks.	63 A
InA	29 A
RDF	0.9
Connection / feeder cable	<ul style="list-style-type: none"> • for 1 kabel opptil 5 x 10 mm²
Kapslingsgrad	IP44
Berøringsbeskyttelse	false
Husmateriale	kunststoff
Vekt	3440 g
Høyde	260 mm
Bredde	225 mm
Kontrollmerke	EAC

Dimensjoner



Drawing 1 MB 521

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	175 mm
	IP 67	194 mm
CEE 16A, 3p, 230V	IP 44	204 mm
	IP 67	205 mm
CEE 16A, 5p, 400V	IP 44	209 mm
	IP 67	213 mm
CEE 32A, 5p, 400V	IP 44	221 mm
	IP 67	227 mm
CEE 63A, 5p, 400V	IP 44	248 mm
	IP 67	248 mm

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.