

Fasevender veggplugg

Bestillingsnr. 3523




- Skrukontakt
- Festes utenfra

Tekniske spesifikasjoner

| | |
|-----------------|-------------|
| Ampere | 32 A |
| Poler | 5 p |
| Volt | 400 V |
| Klokkeposisjon | 6 h |
| Hertz | 50-60 Hz |
| Tilkoblingsmåte | skrukontakt |
| Kontakt | standard |
| Kapslingsgrad | IP44 |
| Vekt | 320 g |
| Kontrollmerke | EAC |

Dimensjoner



| Drawing Z MB 221 | Amp. Poles | 16 | | 32 | | |
|---------------------|---------------|--------|--------|--------|--------|--------|
| | | 4 | 5 | 3 | 4 | 5 |
| Dim. in mm | a | 92.5 | 92.5 | 102 | 102 | 102 |
| | b | 87 | 87 | 94 | 94 | 94 |
| | c | 84.5 | 84.5 | 94 | 94 | 94 |
| | d | 55.5 | 55.5 | 62 | 62 | 62 |
| | e | 76 | 76 | 84 | 84 | 84 |
| | f1 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 |
| | f2 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 |
| | h | 128 | 128 | 146 | 146 | 146 |
| | i | 21.5 | 21.5 | 26 | 26 | 26 |
| | M | 25x1.5 | 25x1.5 | 25x1.5 | 25x1.5 | 32x1.5 |