

## Veggkontakt

Bestillingsnr. 2766A




- Skrukontakt
- intern fastsättning
- en kabelingång i toppen, två blindingånger (kan skæras ut) i botten
- uttag kan høljets bas vridas 180°
- Stikkontakter preparert for montering av hjelpekontaktbryter

## Tekniske spesifikasjoner

Ampere	16 A
Poler	5 p
Volt	690-600 V
Klokkeposisjon	5 h
Hertz	60-50 Hz
Tilkoblingsmåte	skrukontakt
Kontakt	standard
Kapslingsgrad	IP44
Vekt	283 g
Kontrollmerke	CQC

## Dimensjoner



Drawing 1 MB 43	Amp. Poles	16		32		
		4	5	3	4	5
Dim. in mm	a	128	128	128	128	128
	b	84	84	84	84	84
	c	122	124	136	136	138
	d	11	11	11	11	11
	e	68	68	68	68	68
	f	5.3	5.3	5.3	5.3	5.3
	g	4	4	4	4	4
	h	144	145	158	158	160
	M	25	25	32	32	32
	M*	2x25 (blind) to be cut out		2x25 (blind) to be cut out		
	Max. cable diam. (mm)	18	18	18/25	18/25	18/25
	Terminal for cond. cross section (mm <sup>2</sup> ) min.-max.	1.5	1.5	2.5	2.5	2.5
		-4	-4	-10	-10	-10